

KING



Executive armchair with high back and headrest or low back and visitor version.

Seat and back: internal frame in steel with padding in expanded fireproof polyurethane cold injected density min. 60 Kg/m³

Arms:



- **flexible arms** : in flexible steel with upper-injection in integral expanded polyurethane with juncture in die-cast polished aluminium
- **fixed aluminium arms**: in die-cast polished aluminium, padded and upholstered on the top
- **fixed aluminium arms**: in die-cast polished aluminium, with top in black polyurethane
- **adjustable arms** : adjustable in height for **100 mm by Step by Step system** and rotating – **30° inside /30° outside**.

Seat height adjustment: through gas-spring, cone \varnothing 28 mm.

Actions:

Fixed plate: (for version without mechanism) in painted steel thickness 2.5 mm., cone \varnothing 28 mm.

Tilting mechanism : structure in steel and aluminum with the following adjustments:

- Lever for seat height adjustment and tilting movement control lockable in 5 positions
- anti-shock system
- knob for tension adjustment



-“Knee-tilt” mechanism: steel frame with tilting on decentralized axe, with the following adjustments:

- lever for seat height adjustment
- Lever for tilting movement control, lockable in 5 positions
- Antishock system
- Tilting tension adjustment



Only on request: Gas system with automatic return of the chair only for 5-star bases with glides and AL4 base (for versions without mechanism)

Swivel bases:

- **APN** **5-star** base with steel inner frame mm.25x30 thickness 2 mm, with cover in black polypropylene Ø 650 mm. (Ansi-Bifma X5.1-1993/8)
- **APS** **5-star** base in black reinforced nylon Ø 660 mm.
- **APW** **5-star** base in white nylon Ø 675 mm.
- **APG** **5-star** base in grey nylon Ø 675 mm.
- **AL6** **5-star** base in die-cast polished aluminum Ø 654 mm.
- **AL7** **5-star** base in die-cast polished aluminum Ø 650 mm.
- **AL8** **5-star** base in die-cast polished aluminum Ø 650 mm (polished on the top and epoxy black painted on the side part).
- **AL9** **5-star** base in die-cast aluminum painted aluminum Ø 650 mm
- **AL5** **5-star** base in die-cast polished aluminum Ø 654 mm. **with chromed castors** Ø50 mm. and **chromed gaslift.**
- **AL4** 4-star base in die-cast aluminum Ø 730 mm. with chromed feet and **chromed gas-lift.**

Castors: for **APN and AL7:** double self-braking soft castors in nylon Ø 50 mm suitable for hard floors (DIN 68131 – DIN 4551). By request double self-braking hard castors for carpet floors.
For **APS, APW, APG, AL6, AL8, AL9** : double self-braking soft castors in nylon Ø 65 mm suitable for all kind of flooring.
For **AL5:** chromed castors Ø 65 mm.

Fixed frames: sled frame with arms and black polyurethane top, in steel tube Ø 25 mm., black painted (AN), aluminium grey painted (AV) or chromed (AC).

PRODUCT IN ACCORDANCE WITH EUROPEAN STANDARDS EN 1335 – TYPE B

Dimensions:

