

# TRACING LANDSCAPES



Field Study

<b>Construction</b>	Tufted, Textured Loop Pile
<b>Face Fibre</b>	Econyl 100% Solution Dyed Nylon 6
<b>Soil Release</b>	StainSmart® for soil release, liquid repellence - selected colours only (see below)*
<b>Finished Face Weight</b>	560 g/m <sup>2</sup>
<b>Gauge</b>	47.2 / 10 cm
<b>Rows</b>	44 / 10 cm
<b>Tuft Density</b>	207,680 /m <sup>2</sup>
<b>Finished Pile Height</b>	3.6 mm
<b>Standard Backing</b>	Comfort Lite 90% Recycled Open Cell Polyurethane Available with TractionBack® on request
<b>Nominal Total Thickness</b>	9.4 mm
<b>Tile Size</b>	50 cm x 50 cm
<b>Nominal Total Weight</b>	4100 g/m <sup>2</sup>
<b>Tiles per Box</b>	20 (5m <sup>2</sup> )

De Projectinrichter

www.deprojectinrichter.com  
088 - 650 12 34

## PERFORMANCE

<b>Flammability (Euroclassification EN13501:1-2002)</b>	Class Bfl - s1
<b>Flammability (Radiant Panel ASTM-E-648)</b>	Class 1
<b>Flammability (Hot Metal Nut BS4790)</b>	Low Radius of Char
<b>Use Classification (EN 1307)</b>	Class 33 Heavy Commercial Use
<b>Static Electricity (ISO 6356)</b>	Pass ≤ 2.0 KV Permanent Conductive Fibre
<b>Impact Sound (ISO 10140-3)</b>	33 dB
<b>Sound Absorption (ISO354)</b>	0.30 (H) Class D
<b>Alpha s values</b>	125Hz 0.00, 250Hz 0.05, 500Hz 0.30, 1000Hz 0.25, 2000Hz 0.30, 4000Hz 0.35

## ENVIRONMENTAL

- 26% Recycled content by total product weight
- 90% Recycled content cushion backing
- Manufactured in ISO14001 certified location using electricity from renewable sources
- GuT & CRI Green Label Plus certified for indoor air quality

## WARRANTIES

- 12 year wear warranty
- Lifetime Antistatic guarantee
- Latent Defects guarantee

### \*StainSmart® Applied to the following colours only

Etched Valley - High Cliffs - Wind Vane - Misty Mornings,  
Silver Lakes - Grey Moss

## CERTIFICATIONS

--	--	--	--	--	--	--	--	--	--	--

## INSTALLATION



## CE MARKING

--	--	--	--	--	--