

FRACTALS

Enlace / Entangle

www.deprojectinrichter.com
088 - 650 12 34



Construction	Tufted, Luxury Textured Loop Pile
Face Fibre	100% Nylon 6 including 40% ECONYL® recycled fibre
Soil Release	StainSmart® for soil release, liquid repellence
Finished Face Weight	915 g/m ²
Gauge	47.2 / 10 cm
Rows	47.0 / 10 cm
Tuft Density	221,840 /m ²
Finished Pile Height	5.6 mm
Standard Backing	Comfort Plus® 90% Recycled Polyurethane cushion Available with TractionBack® on request
Nominal Total Thickness	11.4 mm
Plank Size	25 cm x 100 cm
Nominal Total Weight	4860 g/m ²
Planks per Box	8 (2m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Cfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	33 dB
Sound Absorption (ISO354)	0.30 (H) Class D
Alpha s values	125Hz 0.03, 250Hz 0.07, 500Hz 0.42, 1000Hz 0.26, 2000Hz 0.36, 4000Hz 0.45

ENVIRONMENTAL

63% recycled content by total product weight
 Manufactured in ISO14001 certified location using renewable sources
 GuT & CRI Green Label Plus certified for indoor air quality
 EPD verified - BRE certified

WARRANTIES

15 year wear warranty
 Lifetime Antistatic guarantee
 Latent Defects guarantee

CERTIFICATIONS

INSTALLATION

Ashlar Random	Herringbone

CE MARKING

13 DOP-0338-100401 EN 14041:2004					